

PRO FLOOD LIGHT

Durable and versatile flood light for various outdoor application.



PRODUCT BENEFITS

- Elegant slim design; reduces windage
- Flicker free for TV Broadcast application
- Excellent glare control; friendly for eyes
- Sophisticated optics design ensuring desired results
- Versatile 360° movement on angle for perfect focus on desired object

MODEL NO	POWER (W)	LUMENS (LM)	EFFICIENCY (LM/W)
OS-E028E-10W	10W	1200 lm	120 lm/w
OS-E028E-20W	20W	2400 lm	120 lm/w
OS-E028E-30W	30W	3600 lm	120 lm/w
OS-E028E-50W	50W	6000 lm	120 lm/w
OS-E028E-100W	100W	12000 lm	120 lm/w
OS-E028E-150W	150W	18000 lm	120 lm/w
OS-E028E-200W	200W	24000 lm	120 lm/w
OS-E028E-250W	250W	30000 lm	120 lm/w
OS-E028E-300W	300W	36000 lm	120 lm/w
OS-E028E-400W	400W	48000 lm	120 lm/w

PRODUCT FEATURES

- Standard CCT: 2500K, 3000K, 4000K, 5300K
- High Color Rendering: CRI>80
- Types of protection: IP66 and IK07
- RGBCW powered by Tuya is available
- Operates at 100-305VAC 50/60Hz
- Product is made up of Die-casting Aluminum
- Beam Angle: 90° is standard, customization is available

- Compatible with DALI Controls
- High Power Factor: $Pf > 0.9$
- Class I Equipment
- Long >50,000 hours lamp lifetime
- Built-in Surge Protection Device
- Working Temperature: -40°C to $+55^{\circ}\text{C}$
- External vent/respirator: Avoids internal fogging and frosting
- Application: Outdoor Security, Parks, Roads, Façade Uplit, Open Areas, Sports Grounds etc.

DIMENSIONS (mm)

MODEL NO	A	B	C	WEIGHT (KG)
OS-E028E-10W	136	120	30	0.35kg
OS-E028E-20W	171	155	37	0.62kg
OS-E028E-30W	207	176	38	0.95kg
OS-E028E-50W	237	210	38	1.28kg
OS-E028E-100W	327	268	48	2.59kg
OS-E028E-150W	370	310	49	3.68kg
OS-E028E-200W	414	343	52	4.72kg
OS-E028E-250W	520	428	56	7.65kg
OS-E028E-300W	520	428	56	7.95kg
OS-E028E-400W	545	436	36	21.9kg

