



Cloud series with a unique shape and proportions, widely use for general lighting applications. Available in multiple diameter sizes from 11.8" up to 47.2"; mounted and suspended, for optional light distributions to fit the scale, with acoustic version for optional.





Features:

- Novel design, beautiful lighting effect;
- High quality material for good reliability;
- Multi-color combination for option;
- Different dimming modes for option: 0-10V, Dali, Triac, RGBW
- Emergency for option;
- Long lifetime and energy efficient.

Application:

Hotel, office, restaurant, public building, etc.



Model	Input Voltage(V)	Power	CRI	CCT (K)	PF	Efficacy (LM/W)	LED	Beam (degree)	Installation	Material	Size(mm) W*H*L	Size(Inch)W*H*L
LL0214AS-40W	AC220-240V or AC120-277V 50/60Hz	40W	≥80 or ≥90	3000K/ 4000K/ 5000K	≥0.9	70	Samsung	300	suspended with 1.5m power cable and safety cable	Silicon+Alu	300*300*18	11.8*11.8*0.71
LL0214AS-50W		50W									400*400*18	15.7*15.7*0.71
LL0214AS-72W		72W									500*500*18	19.7*19.7*0.71
LL0214AS-100W		100W									500*900*18	19.7*35.4*0.71
LL0214AS-150W		150W									1100*650*18	43.3*25.6*0.71
LL0214AM-40W	AC220-240V or AC120-277V 50/60Hz	40W	≥80 or ≥90	3000K/ 4000K/ 5000K	≥0.9	70	Samsung	300	surface mounted	Silicon+Alu	300*300*45	11.8*11.8*1.78
LL0214AM-50W		50W									400*400*45	15.7*15.7*1.78
LL0214AM-72W		72W									500*500*45	19.7*19.7*1.78
LL0214AM-100W		100W									500*900*45	19.7*35.4*1.78
LL0214AM-150W		150W									1100*650*45	43.3*25.6*1.78

