





Features:

- Novel design, beautiful lighting effect;
- High quality material for good reliability;
- Multi-color combination for option;
- Different dimming modes for option: 0-10V, Dali, Triac, RGBW
- Emergency for option;
- Long lifetime and energy efficient.

Application:

Hotel, office, restaurant, public building, etc.



Model	Input Voltage(V)	Power	CRI	CCT (K)	PF	Efficacy (LM/W)	LED	Beam (degree)	Installation	Material	Size(mm) W*H*L	Size(Inch)W*H*L
LL0214ASAC-40W	AC220-240V or AC120-277V 50/60Hz	40W	≥80 or ≥90	3000K/ 4000K/ 5000K	≥0.9	70	Samsung	300	surface mounted	Silicon+Alu+polyester fiber	300*300*28	11.8*11.8*1.1
LL0214ASAC-50W		50W									400*400*28	15.7*15.7*1.1
LL0214ASAC-72W		72W									500*500*28	19.7*19.7*1.1
LL0214ASAC-100W		100W									500*900*28	19.7*35.4*1.1
LL0214ASAC-150W		150W									1100*650*28	43.3*25.6*1.1
LL0214AMAC-40W	AC220-240V or AC120-277V 50/60Hz	40W	≥80 or ≥90	3000K/ 4000K/ 5000K	≥0.9	70	Samsung	300	suspended with 1.5m power cable and safety cable	Silicon+Alu+polyester fiber	300*300*55	11.8*11.8*2.16
LL0214AMAC-50W		50W									400*400*55	15.7*15.7*2.16
LL0214AMAC-72W		72W									500*500*55	19.7*19.7*2.16
LL0214AMAC-100W		100W									500*900*55	19.7*35.4*2.16
LL0214AMAC-150W		150W									1100*650*55	43.3*25.6*2.16