





Doughnut



Suspended



CRI(Ra): ≥ 80 or ≥ 90
 CCT(K): 3000/4000/5000
 PF: ≥ 0.9
 Efficiency(LM/W): 70
 LED type: Samsung
 Beam angle: 360°
 Installation: Suspended with 1.5m power cable and safety cable
 Material: PE
 Body color: White





Model	Power	Input voltage(V)	Size(mm) D*H	Size(Inch) D*H
LL0175S-25W	25W	AC220-240V OR AC120-277V 50/60Hz	D400*60	D15.7*2.6
LL0175S-36W	36W		D600*60	D23.6*2.6
LL0175S-60W	60W		D900*60	D35.4*2.6
LL0175S-80W	80W		D1200*60	D47.2*2.6
LL0175S-100W	100W		D1500*60	D59.0*2.6
LL0175S-120W	120W		D1800*60	D70.8*2.6

Mounted



CRI(Ra): ≥ 80 or ≥ 90
 CCT(K): 3000/4000/5000
 PF: ≥ 0.9
 Efficiency(LM/W): 70
 LED type: Samsung
 Beam angle: 360°
 Installation: Surface mounted
 Material: PE
 Body color: White



Model	Power	Input voltage(V)	Size(mm) D*H	Size(Inch) D*H
LL0175M-25W	25W	AC220-240V OR AC120-277V 50/60Hz	D400*95	D15.7*3.7
LL0175M-36W	36W		D600*95	D23.6*3.7
LL0175M-60W	60W		D900*95	D35.4*3.7
LL0175M-80W	80W		D1200*95	D47.2*3.7
LL0175M-100W	100W		D1500*95	D59.0*3.7
LL0175M-120W	120W		D1800*95	D70.8*3.7