





CRI(Ra): ≥ 80 or ≥ 90
 CCT(K): 3000/4000/5000
 PF: ≥ 0.9
 Efficiency(LM/W): 105
 LED type: Samsung
 Beam angle: 120°
 Input voltage(V): AC220-240V OR AC120-277V 50/60Hz
 Installation: Suspended / Surface Mounted
 Material: Alu+PC



Model	Power	Suspended		Surface Mounted	
		Size(mm) L*W*H	Size(Inch) L*W*H	Size(mm) L*W*H	Size(Inch) L*W*H
LL0188S/M-25W	25W	416*360*85	16.4*14.2*3.4	416*360*75(OD480)	16.4*14.2*3.0
LL0188S/M-40W	40W	520*450*85	20.5*17.7*3.4	520*450*75(OD600)	20.5*17.7*3.0
LL0188S/M-90W	90W	780*675*85	30.7*26.6*3.4	780*675*75(OD900)	30.7*26.6*3.0
LL0188S/M-180W	180W	1039*900*85	40.9*35.4*3.4	1039*900*75(OD1200)	40.9*35.4*3.0



CRI(Ra): ≥ 80 or ≥ 90
 CCT(K): 3000/4000/5000
 PF: ≥ 0.9
 Efficiency(LM/W): 105
 LED type: Samsung
 Beam angle: 120°
 Input voltage(V): AC220-240V OR AC120-277V 50/60Hz
 Installation: Suspended / Surface Mounted
 Material: Alu+PC



Model	Power	Suspended		Surface Mounted	
		Size(mm) L*W*H	Size(Inch) L*W*H	Size(mm) L*W*H	Size(Inch) L*W*H
LL0116S/M-15W	15W	300*300*75	11.8*11.8*3.0	300*300*85	11.8*11.8*3.4
LL0116S/M-40W	40W	600*600*75	23.6*23.6*3.0	600*600*85	23.6*23.6*3.4
LL0116S/M-80W	80W	600*1200*75	23.6*47.2*3.0	600*1200*85	23.6*47.2*3.4
LL0116S/M-160W	160W	1200*1200*75	47.2*47.2*3.0	1200*1200*85	47.2*47.2*3.4
LL0116S/M-320W	320W	1200*2400*75	47.2*94.5*3.0	1200*2400*85	47.2*94.5*3.4

