







CRI(Ra): ≥ 80 or ≥ 90
 CCT(K): 3000/4000/5000
 PF: ≥ 0.9
 Efficiency(LM/W): 85
 LED type: Samsung
 Beam angle: $120^{\circ} \times 2$
 Installation: Suspended with 1.5m power
 cable and safety cable
 Material: Alu+PC
 Body color: White/Black



Model	Power	Input voltage(V)	Size(mm) D*H	Size(inch) D*H
LL0112UDS-50W-PRO	50W	AC220-240V or AC200-277V 50/60Hz	D480*100	D18.9*4.0
LL0112UDS-80W-PRO	80W		D600*100	D23.6*4.0
LL0112UDS-120W-PRO	120W		D900*100	D35.4*4.0
LL0112UDS-220W-PRO	220W		D1200*100	D47.2*4.0





CRI(Ra): ≥ 80 or ≥ 90
CCT(K): 3000/4000/5000
PF: ≥ 0.9
Efficiency(LM/W): 85
LED type: Samsung
Beam angle: 120°
Installation: 1.2m stem mounted
Material: Alu+PC
Body color: White/Black



Model	Power	Input voltage(V)	Size(mm) D*H	Size(inch) D*H
LL0112UDST-50W-PRO	50W	AC220-240V or AC120-277V 50/60Hz	D480*100	D18.9*4.0
LL0112UDST-80W-PRO	80W		D600*100	D23.6*4.0
LL0112UDST-120W-PRO	120W		D900*100	D35.4*4.0
LL0112UDST-220W-PRO	220W		D1200*100	D47.2*4.0



CRI(Ra): ≥ 80 or ≥ 90
CCT(K): 3000/4000/5000
PF: ≥ 0.9
Efficiency(LM/W): 85
LED type: Samsung
Beam angle: $120^{\circ} \times 2$
Installation: Surface mounted
Material: Alu+PC
Body color: White/Black



Model	Power	Input voltage(V)	Size(mm) D*H	Size(inch) D*H
LL0112UDM-50W-PRO	50W	AC220-240V or AC120-277V 50/60Hz	D480*135	D18.9*5.3
LL0112UDM-80W-PRO	80W		D600*135	D23.6*5.3
LL0112UDM-120W-PRO	120W		D900*135	D35.4*5.3
LL0112UDM-150W-PRO	150W		D1200*135	D47.2*5.3