






Features:

- Streamline design style, can be seamless connection with any dimension, with an elegant presentation;
- Can be grouped to different patterns to match the architecture style;
- High efficiency and energy saving;
- Different dimming modes for option: 0-10V, Dali, Triac, RGBW
- Emergency for option;
- Different profile sizes are available to well light up the space!

Application:

Hotel, hospital, shopping mall, showroom, supermarket, office, KTV, museum, cinema, public buildings, etc.



Model	Art.No.	Input Voltage(V)	Power	CRI	CCT (K)	PF	Efficacy (LM/W)	LED	Beam (degree)	Installation	Material	Size(mm) W*H*L	Size(Inch) W*H*L
LL0148R	LL0148R-1200	AC220-240V or AC120-277V 50/60Hz	50W	≥80	3000K/	≥0.9	105	Osram	120	Recessed	Alu+PC	95*75*1200	3.7*3.0*47.2
	LL0148R-1500		70W	or	4000K/							95*75*1500	3.7*3.0*59.1
	LL0148R-2400		100W	≥90	5000K							95*75*2400	3.7*3.0*94.5
LL0149R	LL0149R-1200	AC220-240V or AC120-277V 50/60Hz	50W	≥80	3000K/	≥0.9	105	Osram	120	Recessed	Alu+PC	115*35*1200	4.5*1.4*47.2
	LL0149R-1500		80W	or	4000K/							115*35*1500	4.5*1.4*59.1
	LL0149R-2400		100W	≥90	5000K							115*35*2400	4.5*1.4*94.5

