



Model	Art.No.	Input Voltage(V)	Power	CRI	CCT (K)	PF	Efficacy (LM/W)	LED	Beam (degree)	Installation	Material	Size(mm) W*H*L	Size(Inch) W*H*L
LL0105R	LL0105R-1200	AC220-240V or AC120-277V 50/60Hz	25W	≥80	3000K/ 4000K/ 5000K	≥0.9	105	Osram	120	Recessed	Alu+PC	50*30*1200	2.0*1.2*47.2
	LL0105R-1500		36W	or								50*30*1500	2.0*1.2*59.1
	LL0105R-2400		50W	≥90								50*30*2400	2.0*1.2*94.5
LL0106R	LL0106R-1200	AC220-240V or AC120-277V 50/60Hz	36W	≥80	3000K/ 4000K/ 5000K	≥0.9	105	Osram	120	Recessed	Alu+PC	65*35*1200	2.6*1.4*47.2
	LL0106R-1500		50W	or								65*35*1500	2.6*1.4*59.1
	LL0106R-2400		70W	≥90								65*35*2400	2.6*1.4*94.5
LL0147R	LL0147R-1200	AC220-240V or AC120-277V 50/60Hz	40W	≥80	3000K/ 4000K/ 5000K	≥0.9	105	Osram	120	Recessed	Alu+PC	95*35*1200	3.7*1.4*47.2
	LL0147R-1500		60W	or								95*35*1500	3.7*1.4*59.1
	LL0147R-2400		80W	≥90								95*35*2400	3.7*1.4*94.5