







CRI(Ra): ≥ 80 or ≥ 90
 CCT(K): 3000/4000/5000
 PF: ≥ 0.9
 Efficiency(LM/W): 85
 LED type: Samsung
 Beam angle: 120°
 Installation: 1.2m stem mounted
 Material: Alu+PC
 Body color: White / Black



Model	Power	Input voltage(V)	Size(mm) D*H	Size(Inch) D*H
LL0112ST-15W	15W	AC220-240V or AC220-277V 50/60Hz	D300*80	D11.8*3.1
LL0112ST-20W	20W		D400*80	D14.7*3.1
LL0112ST-25W	25W		D480*100	D18.9*3.9
LL0112ST-40W	40W		D600*100	D23.6*3.9
LL0112ST-90W	90W		D900*100	D35.4*3.9
LL0112ST-180W	180W		D1200*100	D47.2*3.9



CRI(Ra): ≥ 80 or ≥ 90
 CCT(K): 3000/4000/5000
 PF: ≥ 0.9
 Efficiency(LM/W): 85
 LED type: Samsung
 Beam angle: $120^{\circ} \times 2$
 Installation: 4ft stem mounted
 Material: Alu+PC
 Body color: White/Black



Model	Power	Input voltage(V)	Size(mm) D*H	Size(Inch) D*H
LL0112UDST-50W (up 20w, down 30w)	50W	AC220-240V or AC120-277V 50/60Hz	D480*80	D18.9*3.1
LL0112UDST-80W (up 30w, down 50w)	80W		D600*80	D23.6*3.1
LL0112UDST-120W (up 48w, down 72w)	120W		D900*80	D35.4*3.1
LL0112UDST-220W (up 88w, down 132w)	220W		D1200*80	D47.2*3.1

