



LL0112S





LL0112M

Features:

- Novel design, beautiful lighting effect;
- High quality material for good reliability;
- Multi-color combination for option;
- Different dimming modes for option: 0-10V, Dali, Triac, RGBW
- Emergency for option;
- Long lifetime and energy efficient.

Application:

Hotel, office, restaurant, public building, etc.



Model	Art.No.	Input Voltage(V)	Power	CRI	CCT (K)	PF	Efficacy (LM/W)	LED	Beam (degree)	Installation	Material	Size(mm) D*H	Size(Inch) D*H
LL0112S	LL0112S-15W	AC220-240V or AC120-277V 50/60Hz	15W	≥80 or ≥90	3000K/ 4000K/ 5000K	≥0.9	85	Samsung	120	Suspended	Alu+PC	D300*80	D11.8*3.1
	LL0112S-20W		20W									D400*80	D15.7*3.1
	LL0112S-25W		25W									D480*80	D18.9*3.1
	LL0112S-40W		40W									D600*80	D23.6*3.1
	LL0112S-90W		90W									D900*80	D35.4*3.1
	LL0112S-180W		180W									D1200*80	D47.2*3.1
LL0112M	LL0112M-15W	AC220-240V or AC120-277V 50/60Hz	15W	≥80 or ≥90	3000K/ 4000K/ 5000K	≥0.9	85	Samsung	120	Surface Mounted	Alu+PC	D300*95	D11.8*3.7
	LL0112M-20W		20W									D400*95	D15.7*3.7
	LL0112M-25W		25W									D480*95	D18.9*3.7
	LL0112M-40W		40W									D600*95	D23.6*3.7
	LL0112M-90W		90W									D900*95	D35.4*3.7
	LL0112M-150W		150W									D1200*95	D47.2*3.7