







Up and Down



Model	Input Voltage(V)	Power	CRI	CCT (K)	PF	Efficacy (LM/W)	LED	Beam (degree)	Installation	Material	Size(mm) W*H*L	Size(Inch) W*H*L
LL0186M-25W	AC220-240V or AC120-277V 50/60Hz	25W	≥80 or ≥90	3000K/ 4000K/ 5000K	≥0.9	85	Samsung	120	Surface Mounted	Alu+PC	480*46*95(ID480)	18.9*16.4*3.7
LL0186M-40W		40W									600*520*95(ID600)	23.6*20.5*3.7
LL0186M-90W		90W									900*780*95(ID900)	35.4*30.7*3.7
LL0186M-180W		180W									1200*1040*95(ID1200)	47.2*40.9*3.7
LL0186S-25W	AC220-240V or AC120-277V 50/60Hz	25W	≥80 or ≥90	3000K/ 4000K/ 5000K	≥0.9	85	Samsung	120	Suspended	Alu+PC	480*46*80(ID480)	18.9*16.4*3.1
LL0186S-40W		40W									600*520*80(ID600)	23.6*20.5*3.1
LL0186S-90W		90W									900*780*80(ID900)	35.4*30.7*3.1
LL0186S-180W		180W									1200*1040*80(ID1200)	47.2*40.9*3.1
LL0186UDM-50W	AC220-240V or AC120-277V 50/60Hz	50W	≥80 or ≥90	3000K/ 4000K/ 5000K	≥0.9	85	Samsung	120*2	Surface Mounted	Alu+PC	480*46*95(ID480)	18.9*16.4*3.7
LL0186UDM-80W		80W									600*520*95(ID600)	23.6*20.5*3.7
LL0186UDM-120W		120W									900*780*95(ID900)	35.4*30.7*3.7
LL0186UDM-220W		220W									1200*1040*95(ID1200)	47.2*40.9*3.7
LL0186UDS-50W	AC220-240V or AC120-277V 50/60Hz	50W	≥80 or ≥90	3000K/ 4000K/ 5000K	≥0.9	85	Samsung	120*2	Suspended	Alu+PC	480*46*80(ID480)	18.9*16.4*3.1
LL0186UDS-80W		80W									600*520*80(ID600)	23.6*20.5*3.1
LL0186UDS-120W		120W									900*780*80(ID900)	35.4*30.7*3.1
LL0186UDS-220W		220W									1200*1040*80(ID1200)	47.2*40.9*3.1