







Up and Down



Model	Input Voltage(V)	Power	CRI	CCT (K)	PF	Efficacy (LM/W)	LED	Beam (degree)	Installation	Material	Size(mm) W*H*L	Size(Inch) W*H*L
LL0185M-25W	AC220-240V or AC120-277V 50/60Hz	25W	≥80 or ≥90	3000K/ 4000K/ 5000K	≥0.9	85	Samsung	120	Surface Mounted	Alu+PC	480*480*95	18.9*18.9*3.7
LL0185M-40W		40W									600*600*95	23.6*23.6*3.7
LL0185M-90W		90W									900*900*95	35.4*35.4*3.7
LL0185M-180W		180W									1200*1200*95	47.2*47.2*3.7
LL0185S-25W	AC220-240V or AC120-277V 50/60Hz	25W	≥80 or ≥90	3000K/ 4000K/ 5000K	≥0.9	85	Samsung	120	Suspended	Alu+PC	480*480*80	18.9*18.9*3.1
LL0185S-40W		40W									600*600*80	23.6*23.6*3.1
LL0185S-90W		90W									900*900*80	35.4*35.4*3.1
LL0185S-180W		180W									1200*1200*80	47.2*47.2*3.1
LL0185UDM-50W	AC220-240V or AC120-277V 50/60Hz	50W	≥80 or ≥90	3000K/ 4000K/ 5000K	≥0.9	85	Samsung	120*2	Surface Mounted	Alu+PC	480*480*95	18.9*18.9*3.7
LL0185UDM-80W		80W									600*600*95	23.6*23.6*3.7
LL0185UDM-120W		120W									900*900*95	35.4*35.4*3.7
LL0185UDM-220W		220W									1200*1200*95	47.2*47.2*3.7
LL0185UDS-50W	AC220-240V or AC120-277V 50/60Hz	50W	≥80 or ≥90	3000K/ 4000K/ 5000K	≥0.9	85	Samsung	120*2	Suspended	Alu+PC	480*480*80	18.9*18.9*3.1
LL0185UDS-80W		80W									600*600*80	23.6*23.6*3.1
LL0185UDS-120W		120W									900*900*80	35.4*35.4*3.1
LL0185UDS-220W		220W									1200*1200*80	47.2*47.2*3.1