



Model	Input Voltage(V)	Power	CRI	CCT (K)	PF	Efficacy (LM/W)	LED	Beam (degree)	Installation	Material	Size(mm) D*W*H	Size(Inch) D*W*H
LL0125S-32W	AC220-240V or AC120-277V 50/60Hz	32W	≥80 or ≥90	3000K/ 4000K/ 5000K	≥0.9	70lm/w	Samsung	300	Suspended	Alu+PC	D600*35*32	D23.6*1.4*1.3
LL0125S-40W		40W									D900*35*32	D35.4*1.4*1.3
LL0125S-70W		70W									D1200*35*32	D47.2*1.4*1.3
LL0125S-80W		80W									D1500*35*32	D59.1*1.4*1.3
LL0125M-32W	AC220-240V or AC120-277V 50/60Hz	32W	≥80 or ≥90	3000K/ 4000K/ 5000K	≥0.9	70lm/w	Samsung	300	Mounted	Alu+PC	D600*35*32	D23.6*1.4*1.3
LL0125M-40W		40W									D900*35*32	D35.4*1.4*1.3
LL0125M-70W		70W									D1200*35*32	D47.2*1.4*1.3
LL0125M-80W		80W									D1500*35*32	D59.1*1.4*1.3
LL0126S-32W	AC220-240V or AC120-277V 50/60Hz	32W	≥80 or ≥90	3000K/ 4000K/ 5000K	≥0.9	70lm/w	Samsung	300	Suspended	Alu+PC	D600*35*32	D23.6*1.4*1.3
LL0126S-40W		40W									D900*35*32	D35.4*1.4*1.3
LL0126S-70W		70W									D1200*35*32	D47.2*1.4*1.3
LL0126S-80W		80W									D1500*35*32	D59.1*1.4*1.3
LL0126M-32W	AC220-240V or AC120-277V 50/60Hz	32W	≥80 or ≥90	3000K/ 4000K/ 5000K	≥0.9	70lm/w	Samsung	300	Mounted	Alu+PC	D600*35*32	D23.6*1.4*1.3
LL0126M-40W		40W									D900*35*32	D35.4*1.4*1.3
LL0126M-70W		70W									D1200*35*32	D47.2*1.4*1.3
LL0126M-80W		80W									D1500*35*32	D59.1*1.4*1.3