







CRI(Ra): ≥ 80 or ≥ 90
 CCT(K): 3000/4000/5000
 PF: ≥ 0.9
 Efficiency(LM/W): 70
 LED type: Samsung
 Beam angle: 360°
 Installation: Vertical Suspended
 Material: PMMA
 Body color: Milk White



Model	Power	Input voltage(V)	Size(mm) D*H	Size(Inch) D*H
LL0178-HS-D30-300	6W	AC220-240V or AC120-277V 50/60Hz	300*30	11.8*1.2
LL0178-HS-D30-600	12W		600*30	23.6*1.2
LL0178-HS-D30-900	18W		900*30	35.4*1.2
LL0178-HS-D30-1200	24W		1200*30	47.2*1.2
LL0178-HS-D30-1500	30W		1500*30	59.1*1.2





CRI(Ra): ≥ 80 or ≥ 90
 CCT(K): 3000/4000/5000
 PF: ≥ 0.9
 Efficiency(LM/W): 70
 LED type: Samsung
 Beam angle: 360°
 Installation: Vertical Suspended
 Material: PMMA
 Body color: Milk White



Model	Power	Input voltage(V)	Size(mm) D*H	Size(Inch) D*H
LL0178-HS-D50-300	6W	AC220-240V or AC120-277V 50/60Hz	300*50	11.8*2.0
LL0178-HS-D50-600	12W		600*50	23.6*2.0
LL0178-HS-D50-900	18W		900*50	35.4*2.0
LL0178-HS-D50-1200	24W		1200*50	47.2*2.0
LL0178-HS-D50-1500	30W		1500*50	59.1*2.0



CRI(Ra): ≥ 80 or ≥ 90
 CCT(K): 3000/4000/5000
 PF: ≥ 0.9
 Efficiency(LM/W): 70
 LED type: Samsung
 Beam angle: 360°
 Installation: Vertical Suspended
 Material: PMMA
 Body color: Milk White



Model	Power	Input voltage(V)	Size(mm) D*H	Size(Inch) D*H
LL0178-HS-D80-300	6W	AC220-240V or AC120-277V 50/60Hz	300*80	11.8*3.15
LL0178-HS-D80-600	12W		600*80	23.6*3.15
LL0178-HS-D80-900	18W		900*80	35.4*3.15
LL0178-HS-D80-1200	24W		1200*80	47.2*3.15
LL0178-HS-D80-1500	30W		1500*80	59.1*3.15