

HIGH BAY LIGHT


Highly efficient and enduring luminaire for public areas and industrial halls



PRODUCT BENEFITS

- Very stable & robust design for rough environment
- Eye Safety according to IEC
- Excellent glare control; friendly for eyes
- Compact and slim design
- Sophisticated optics design ensuring desired results
- Highly efficient product ensuring great power saving
- Also suitable for cold storage units

DIMENSIONS (mm)



MODEL	A	B	WEIGHT (KG)
OS-H001E-100W	Ø250	143	1.63
OS-H001E-150W	Ø250	143	2.00
OS-H001E-200W	Ø360	144	2.38
OS-H001E-250W	Ø360	144	3.00

MODEL NO	POWER (W)	LUMENS (LM)	EFFICIENCY (LM/W)
OS-H001E-100W	100W	16000 lm	160 lm/w
OS-H001E-150W	150W	24000 lm	160 lm/w
OS-H001E-200W	200W	32000 lm	160 lm/w
OS-H001E-250W	250W	40000 lm	160 lm/w

PRODUCT FEATURES

- Standard CCT: 3000K, 4000K, 5300K, 6500K
- High Color Rendering: CRI>80
- Types of protection: IP65 and IK08
- Working Temperature: -40°C to +55°C
- Can be integrated with PIR and microwave motion sensors
- High Power Factor: Pf> 0.9
- Class I Equipment
- Long >50,000 hours lamp lifetime
- Operates at 100-305VAC 50/60Hz
- Product is made up of Die-casting Aluminum
- Beam Angle: 90° is standard, customization is available
- Built-in Surge Protection Device
- Application: Warehouses, Public Areas, Factory Sheds, Working Halls etc.